
\$5<mark>,359</mark>





Spot-Rite™ 3-Stage Front Arm Design

accommodates vehicle spotting both symmetrically and asymmetrically. Position the vehicle doors in front of or behind the lift columns to prevent door damage and allow easy technician access!



Click HERE to shop online!

123 S Main St

NAPA PARTS PLACE MILFORD (BANNER DR) 45 Banner Dr Milford, CT 06460 Phone: (203) 874-6706

NAPA PARTS PLACE- MILFORD AUTO SUPPLY 1051 BRIDGEPORT AVE MILFORD, CT 06460 Phone: (203) 874-6776

172 Cedar St Branford, CT 06405 Phone: (203) 488-6336

NAPA PARTS PLACE NEW HAVEN 1329 STATE ST **NEW HAVEN, CT 06511** Phone: (203) 787-5809

NAPA PARTS PLACE BRANFORD

NAPA PARTS PLACE CHESHIRE 25 Jinny Hill Rd Cheshire, CT 06410 Phone: (203) 272-5329

NAPA PARTS PLACE WEST HAVEN **757 1ST AVE** WEST HAVEN, CT 06516 Phone: (203) 933-1651

FEATURES:

Symmetrical column design

LIGHT DUTY TWO POST LIFT

Spot-Rite™ 3-stage front arm design - spot vehicles asymmetrically or symmetrically

10,000 lbs. Capacity

- Top mounted Direct-Pull lifting technology
- · Cylinder rod concealed inside carriage
- · Adjustable width options
- Single point lock release
- · Powder coated finish
- · Includes adapter storage bracket
- ALI Certified

SPECIFICATIONS I10N400MBL/RD* 10,000 lbs. (4535kg) Capacity Maximum rise 76 -1/4" (1937mm) w/5" extension Overall Height 143" (3632mm) Overall Width 131" or optional 137" (3327mm/4380mm) Drive through clearance 99" (2515mm) or optional 105" (2667mm) 137-5/8" (3496mm) Overhead switch height 23" / 44-3/8" (584mm/1127mm) Front reach (Min/Max) Rear reach (Min/Max) 36" / 58" (914mm/1473mm) 3-3/4" (95mm) w/o adapter extension Min/Max adapter height 8-3/4" (222mm) w/ 5" adapter extension Width inside column 109" or optional 115" (2769mm/2921mm) Voltage/ Amps 208V/230V, 17 amps 1ph/2HP/60Hz Motor/Phase 144" (3658mm) Ceiling height required

Specifications subject to change without notice or liability

Naugatuck, CT 06770 Phone: (203) 729-5231

NAPA PARTS PLACE NAUGATUCK